

Residential grade silencers are best suitable for applications where a moderate level of sound attenuation is required. Typical sound attenuation for this grade is in the range of 18 to 24 dB(A) on diesel and gaseous fueled reciprocating industrial engines.

**Standard Features**

- Continuously welded heavy duty steel construction
- Dual chamber design
- Dual wall outer shell to reduce break out noise
- NPT connections up to 4" sizes
- ANSI 125/150# flanges 4" and larger
- High Temperature black finish – rated to 1000F

**Optional Features & Configurations**


- Dual inlets
- Spark Arresting
- Special Flanges / Port Connections
- Mounting Brackets
- Support Structures

**Material & Finishing options available**

- Aluminized outer shell and external heads
- Metallized Aluminum Spray Coat Finish with 100% protected outer surfaces
- High performance paint options
- Custom Aluminum Lagging
- Stainless steel – 304, 316, 321



CSR-06 in 316 stainless

**Typical Sound Attenuation - CSR**

**DIMENSIONS (Inches)**

Model	A	B	C	D	F	G	H	Weight (Lbs.)
CSR-15	1.5	8	20	14	3.5	7	17	14
CSR-02	2	10	20	14	4	8	17	16
CSR-25	2.5	10	24	18	4.5	8	21	21
CSR-03	3	12	26	20	5	9	23	30
CSR-35	3.5	14	30	24	5.5	10	27	46
CSR-04	4	14	36	28	6	11	32	59
CSR-05	5	16	43	35	7	12	39	79
CSR-06	6	18	49	41	7.5	13	45	100
CSR-08	8	22	59	51	9.5	15	55	156
CSR-10	10	26	64	56	11.5	17	60	290
CSR-12	12	30	77	69	13	19	73	400
CSR-14	14	36	83	73	15.5	23	78	515
CSR-16	16	40	90	80	16.5	25	85	797
CSR-18	18	42	96	86	18	26	91	1175

